

NU Series Self Contained Dice Ice Machines – up to 100kg

NU 220 AS Dice cube 10g, 22mm x 22mm x 22mm

NUH 220 AS Half dice cube 6g, 22mm x 22mm x 28mm



Dice cube 10 g
W 22 x D 22 x H 22 mm



Half dice cube 6 g
W 10 x D 22 x H 28 mm




Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.

- Up to 100kg daily production rate
- 37kg storage bin capacity
- Air cooled version
- Agion Technology resists the growth of microbes and the development of unpleasant odours
- Vertical evaporator spray-system technology
- Front-in and front-out air flow designed for placement in tight spaces
- Ergonomic access to ice with sliding disappearing door
- One touch cleaning for time and labour saving
- Resistant stainless steel exterior
- Easy access front condenser air filter
- Routine maintenance visible alarm light on front panel
- Includes removable air filter, ice scoop, water and drain hose



NU Series Self Contained Dice Ice Machines – up to 100kg

NU 220 AS, NUH 220 AS



moffat.com.au

Australia
Moffat Pty Limited
Victoria/Tasmania
740 Springvale Road
Mulgrave, Victoria 3170
Telephone 03-9518 3888
Facsimile 03-9518 3833
vsales@moffat.com.au

New South Wales
Telephone 02-8833 4111
nswsales@moffat.com.au

South Australia
Telephone 03-9518 3888
vsales@moffat.com.au

Queensland
Telephone 07-3630 8600
qldsales@moffat.com.au

Western Australia
Telephone 08-9413 2400
wasales@moffat.com.au

Ice production per 24 hours

Ambient temperature / Water temperature

	10°C / 10°C	21°C / 10°C	32°C / 21°C
NU 220 AS	109	100	70
NUH 220 AS	104	98	65

Dimensions

Width: 651mm
Depth: 690mm
Height: 870mm (including feet)
Nett weight: 61kg
Packed weight: 70kg

Water consumption

Air cooled version:
NU 220 AS: 4.8 litres per hour
NUH 220 AS: 4.5 litres per hour

Electrical rating

Air cooled version: 230-240V, 1P+N+E, 50Hz, 600W,
10A cordset supplied

No. Circuit wire: 3
Compressor: 1300W
Energy consumption: 15.6kW/hr

Refrigerant type

R404a

Installation distance from wall

Rear 100mm
Sides 100mm

Operating requirement air temperature 10-43°C

Water connection requirements

Inlet connection: R ¾"
Cold water: 5-38°C
Pressure: 100-500kPa
Water outlet connection: Ø ¾"

Important Notice:

Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.



© Copyright Moffat Ltd
AU.SM.1904

an Ali Group Company



The Spirit of Excellence